


distribution&marketing(pty)ltd www.atdm.co.za

WORKSHOP PRODUCTS AND CONSUMABLES



KZN: +27 84 469 5953 • Email: darren@fortron.co.za • HO: Tel: 012 653 5606 • admin@fortron.co.za Unit 1, Future Insight Industrial Forum, 7 Stevenson Nook, Hennopspark, Centurion_0157

WARNING

Advanced Petrol System Cleaner

AUTOMOTIVE TECHNOLOGIES distribution & marketing (pty) ltd www.atdm.co.za

325 ml



Website: www.atdm.co.za Reg No. 2008/017115/07

Safety Data Sheet ATDM Advanced Petrol System Cleaner (A-EP)

Issue 1 Dated: 15 January 2022 Doc no: A-EP 01 Page 2 of 9

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Identification of the preparation		
Product Name: ATDM Advanced Petrol System Cleaner		
Product Code: A-EP		
1.2 Identification of the Company		
Manufacturer:	ATDM (PTY) Ltd	
Address:	Unit 1, Future Insight Industrial Forum, 7 Stevenson Nook, Hennopspark, Centurion 0157	
Country:	South Africa	
Telephone:	Tel: 012 653 5606	
Email	admin@fortron.co.za	
Emergency Phone Number:	0832909240	

2. HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture	
Classification under CLP:	Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 3: H226;
	Skin Irrit. 2: H315; STOT SE 3: H336
Most important adverse effects	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2 Label elements	
Hazard statements:	 H226: Flammable liquid and vapour H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation H336: May cause drowsiness or dizziness
Hazard Pictograms:	H411: Toxic to aquatic life with long lasting effects. GHS02: Flame GHS07: Exclamation mark GHS08: Health Hazard GHS09: Environmental

Signal Words:	Danger
Precautionary statements:	 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+310: IF SWALLOWED: Immediately call a POISON CENTRE doctor/first aid P331: Do NOT induce vomiting. P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. P332+313: If skin irritation occurs: Get medical advice/attention.

PBT:	This product is not identified as a PBT/vPvB substance

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Γ

Hazardous Ingredients:

KEROSINE (PET	ROLEUM), HYDR	ODESULPHURIZED		
EINECS	CAS	PBT/WEL	CLP Classification	Percent
265-184-9	64742-81-0		Flam. Liq. 3: H226; Skin Irrit. 2: H315; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; STOT SE 3: H336	>70%

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-2119463258-33-XXXX

EINECS	CAS	PBT/WEL	CLP Classification	Percent
919-857-5	64742-48-9		Flam. Liq. 3: H226; STOT SE 3: H336; Asp. Tox. 1: H304; -: EUH066	1-10%

POLYOLEFIN ALKYL PHENOL ALKYL AMINE				
EINECS	CAS	PBT/WEL	CLP Classification	Percent
NONE	PROPRIETRY	—	Skin Irrit. 2: H315	1-10%

2-ETHYLHEXAN-1-OL				
EINECS	CAS	PBT/WEL	CLP Classification	Percent
203-234-3	104-76-7	_	STOT SE 3: H335; Acute Tox. 4: H332; Skin Irrit. 2: H315; Eye Irrit. 2: H319	<1%

3.2 Mixtures

Non-classified ingredients:

BENZENESULFONIC ACID, DI-C10-14-ALKYL DERIVS, CALCIUM SALTS - REACH registered number(s): 01-2119978241-36-XXXX

EINECS	CAS	PBT/WEL	CLP Classification	Percent
939-603-7	—	—	Skin Sens. 1B: H317	<1%

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL) - REACH registered number(\$): 01-2119490100-53

EINECS	CAS	PBT/WEL	CLP Classification	Percent
931-329-6	68155-07 -7	_	Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315	<1%

4. FIRST AID MEASURES

4.1 Description of fir	4.1 Description of first aid measures	
Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.		
Eye contact:	ontact: Bathe the eye with running water for 15 minutes.	
Ingestion:	Do not induce vomiting. Wash out mouth with water. Consult a doctor	
Inhalation: Move to fresh air in case of accidental inhalation of vapours.		

4.2 Most important symptoms and effects, both acute and delayed		
Skin contact: There may be irritation and redness at the site of contact.		
Eye contact: There may be irritation and redness.		
Ingestion:	stion: Nausea and stomach pain may occur. There may be vomiting and diarrhoea	
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.		
confusion may occur.		

 4.3 Indication of any immediate medical attention and special treatment needed

 Immediate/ Special Treatment:
 Do not induce vomiting. Eye bathing equipment should be available on the premises.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media:	Water spray. Carbon dioxide. Alcohol resistant foam. Dry chemical
	powder. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture	
Exposure hazards:	Flammable. In combustion emits toxic fumes.

5.3 Advice for fire-fighters

Advice for fire-fighters:

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures		
Personal precautions:	Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.	
6.2 Environmental precautions		
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.	
6.3 Methods and material for containment and cleaning up		
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.	
6.4 Reference to other sections		
Reference to other sections	Refer to section 8 of SDS	

7. HANDLING AND STORAGE

7.1 Handling and storage		
Handling requirements:	Ensure there is sufficient ventilation of the area.	
7.2 Conditions for safe storage, including any incompatibilities		
Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition.		
Suitable packaging:	Must only be kept in original packaging.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8	8.1 Control parameters				
Н	azardous ingredients:				
	HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS				
ĺ	Workplace exposure limits:			Respirable dust	
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
	EU	_	—	1000mg/m3	—
	DNEL/PNEC No data				

8.2 Exposure controls		
Engineering measures: Ensure there is sufficient ventilation of the area.		
Respiratory protection:	Respiratory protection not required.	
Hand protection: Gloves (solvent-resistant). Breakthrough time of the glove material > 4 hours		
Eye protection: Safety glasses. Ensure eye bath is to hand.		
Skin protection: Protective clothing.		
Environmental:	Prevent from entering in public sewers or the imediate environment.	

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic phy	vsical and chemical properties		
State:	Liquid	Flammability limits %: lower:	No data available
Colour:	Red	Flash point°C:	42
Odour:	Solvent	Autoflammability°C:	>200
Evaporation rate	Moderate	Relative density:	0.815
Oxidising:	Not applicable	VOC g/l:	No data available
Solubility in water:	Miscible	Melting point/range°C:	<0°c
Also soluble in:	Most organic solvents	upper:	No data available.
Viscosity:	Non- viscous	Part.coeff. n-octanol/water:	No data available
Kinematic viscosity:	<=20.5	Vapour pressure:	approx 2.9 kPa @20°
Viscosity test method:	Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)	pH:	Not applicable
Boiling point/range°C:	140-310		

9.2 Other information

Other information:

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity	
Reactivity:	Stable under recommended transport or storage conditions
10.2 Chemical stability	
Chemical stability:	Stable under normal conditions
10.3 Possibility of hazardous reaction	
Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
10.4 Conditions to avoid	
Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames

10.5 Incompatible materials		
Materials to avoid: Oxidising agents. Reducing agents		
10.6 Hazardous decomposition products		
Haz. decomp. products: In combustion emits toxic fumes.		

11. TOXICOLOGICAL INFORMATION

ardous Ingredients:			
KEROSINE (PETROLEUM) H	IYDRODESULPHURISEI)	
DERMAL	RBT	LD50	>2000mg/kg
HYDROCARBONS, C9-C11,	N-ALKANES, ISOALKAN	ES, CYCLICS, <2% AROMAT	ICS
DERMAL	RBT	LD50	>5000mg/kg
ORAL	RAT	LD50	>5000mg/kg
VAPOURS	RAT	LD50	>4.95mg/l
2-ETHYLHEXAN-1-OL			
ORAL	RAT	LD50	2047mg/kg
VAPOURS	RAT	LD50	0.89mg/l
AMIDES, C8-18 (EVEN NUMI	BERED) AND C18-UNSA	TD, N,N-BIS(HYDROXYETHY	Ľ)
DERMAL	RAT	LD50	>2000mg/kg
ORAL	RAT	LD50	>5000mg/kg
Relevant hazards for product:			
Hazard	Route	Basis	
Skin corrosion/irritation	DRM	Hazardous: calcu	lated
STOT-single exposure	-	Hazardous: calcu	lated
Aspiration hazard	-	Hazardous: calcu	lated

Symptoms/routes of exposure		
Skin contact: There may be irritation and redness at the site of contact.		
Eye contact:	There may be irritation and redness.	
Ingestion:	Nausea and stomach pain may occur. There may be vomiting and diarrhoea	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.	

12. ECOLOGICAL INFORMATION

12.1 Toxicity		
Hazardous ingredients:		
HYDROCARBONS, C9-C11, N-ALKANES, ISO	DALKANES, CYCLICS, <	<2% AROMATICS
Daphnia magna	48H EC50	>1000mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000mg/l
AMIDES, C8-18 (EVEN NUMBERED) AND C1	8-UNSATD, N, N-BIS (H	YDROXYETHYL)
ALGAE	72H IC50	3.9mg/l
DAPHNIA	72H ErC50	3.2mg/l
FISH	96H LC50	2.4mg/l
12.2 Persistence and degradability		
Persistence and degradability: Biodegradable.		
12.3 Bioaccumulative potential	I	
Bioaccumulative potential Bioaccumulation potential.		
12.4 Mobility in soil		
Mobility Volatile. Soluble in water. Floats on water		
12.5 Results of PBT and vPvB assessment		
		identified as a DRT/vDvP substance
	This product is not identified as a PBT/vPvB substance	
12.6 Other adverse effects		
Other adverse effects Toxic to aquatic organisms		anisms
13. DISPOSAL CONSIDERATIONS		
13. DIGI COAL CONCIDERATIONS		
13.1 Waste treatment Methods		
Disposal operations:	specialised disposa	le container and arrange for collection by al company. NB: The user's attention is drawn to

disposal.

the possible existence of regional or national regulations regarding

14. TRANSPORT INFORMATION

14.1 UN number

UN1993

14.2 UN Proper shipping name			
Shipping name:	Flammable Liquid, NOS (KEROSINE (PETROLEUM), HYDRODESULPHURIZED)		
14.3 Transport hazard classes			
Transport class	3		
14.4 Packing group			
Packing group	III		
14.5 Environmental hazards			
Environmentally hazardous	Yes		
Environmentally hazardous Marine pollutant	Yes Yes		
-			
Marine pollutant			
Marine pollutant 14.6 Environmental hazards	Yes		

15. SAFETY, HEALTH & ENVIRONMENTAL REGULATIONS

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

15.2 Chemical Safety Assessment

16. OTHER INFORMATION

16.1 Other information

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3:EUH066: Repeated exposure may cause skin dryness or cracking.
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction
H318: Causes serious eye damage
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Further Information

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.